

Valve

Product Numbers

PV-70-10, PV 70-12 and PV-70-18

Description

PE double O-ring infusion valve. Available in 10 mm, 12 mm, and 18 mm o.d. Maximum use temperature 100°C (212°F).



Technical Data

Part Number	Material	Outside Dia.		Max Temp	
PV-70-10	PE	10 mm	0.39"	100°C	212°F
PV-70-12	PE	12 mm	0.47"	100°C	212°F
PV-70-18	PE	18 mm	0.71"	100°C	212°F

Resin Inlet

Product Number

PV-72-16

Description

Infusion inlet block. 16 mm diameter. Self-seals with Resin Inlet Connector (PV-73) and Omega Resin Feed (PV-64). Can be used up to 100°C (212°F).



Part Number	Material	Interior Dia.		Height		Max Temp	
PV-72-16	PE	16 mm	0.63"	35 mm	1.38"	100°C	212°F



Resin Inlet Connector

Product Numbers

PV-73-12 and PV-73-18

Description

PE, L connector for inlet block. Reducer to 12 mm o/d and expander to 18 mm o/d. Can be used up to 100°C (212°F).



Technical Data

Part Number	Material	Outside Dia.		Shape	Max Temp	
PV-73-12	PE	12 mm	0.47"	L	100°C	212°F
PV-73-18	PE	18 mm	0.71"	L	100°C	212°F

T Connector

Product Numbers

PV-76-10, PV-76-12, and PV-76-18

Description

PE, T connectors for resin infusion. Available in 10 mm, 12 mm, and 18 mm o/d. Can be used up to 100°C (212°F).



Part Number	Material	Outside Dia.		Shape	Max Temp	
PV-76-10	PE	10 mm	0.39"	T	100°C	212°F
PV- 76-12	PE	12 mm	0.47"	T	100°C	212°F
PV- 76-18	PE	18 mm	0.71"	T	100°C	212°F



L Connector

Product Number

PV-77-10

Description

PE, L connector for resin infusion. Available in 10 mm. Can be used up to 100°C (212°F).



Part Number	Material	Outside Dia.		Shape	Max Temp	
PV-77-10	PE	10 mm	0.39"	L	100°C	212°F

